

8000D Linerless



Available
from stock
on ZipShip

Media Type	Label	✓	Adhesive Type	Permanent	✓
	Receipt			Removable	
	Tag			No Adhesive	
	Wristband		Environment	Indoor	✓
Material Type	Paper	✓		Outdoor	
	Synthetic		Properties	Cold Temperature	✓
Printing Technology	Direct Thermal (no Ribbon Required)	✓		Deep Freeze	✓
	Thermal Transfer (Ribbon Required)			High Temperature	
Finish	Matte			Ultra High Temperature	
	Gloss	✓		High Tack	
			Chemical Resistance	-	

Note: 8000D Linerless will require a linerless roller for the printer and is not recommended for applications involving chemicals.

Additional Features

- No ribbon required for direct thermal printing, therefore only one stock item needed
- Absence of a liner allows for more labels per roll and no waste having both environmental and safety implications in some applications
- Good scratch and smear resistance
- Excellent print quality when used in a Zebra linerless printer
- BPA free, BPS free
- Latex free adhesive

Suggested Applications

- Product and price labelling in retail applications
- Mobile point of sale labelling
- Work in progress labelling
- Applications that do not allow the use of a liner

Technical Specifications

	Description	Caliper
Facestock	Smooth white silicone topcoated paper	76 microns
Adhesive	Permanent rubber adhesive	30 microns
	Total	106 microns ±10%

Recommended Zebra Printers:	QL and QLn Series mobile printers
Minimum Application Temperature: When the label is applied, the environment and surface should be above this temperature	4°C
Service Temperature Range: Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range	-40°C to 60°C
Recommended Storage Conditions: Storage of product before use	6 months duration when stored at 22°C at 50% RH
Expected Life Span in Application: Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated	Indoor use, up to 1 year

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order LD-R2LS5W and LD-R4LF5P from the ZipShip price list.